

PTZ CAMERAS

PTZ2001 & PTZ1001

To order,
call
1-888-347-3821

Specifications

TV Type	NTSC
Effective Pixels	768(H) X 494(V) Pixel
Horizontal Resolution	More than 480 TV Lines
Image Sensor	1/4" Sony CCD
Minimum Illumination	0.001 Lux (F1.2)
Scanning System	2:1 Interlace
Video Output	Composite 1.0Vp-p/75
Electric Auto Iris	1/60 ~ 1/100,000 sec
Gamma	0.45
S/N Ratio	Over 45dB (AGC Off)
Pan, Tilt Range	360°(Endless)/180°
Pan, Tilt Speed	Up to 360° /Sec., Up to 90° /Sec
Preset/Pattern /Swing/Group	128 Preset/4 Pattern (1 Min./Pattern)/8 Swing/8 Group
Communication	RS-485 (Max. 99 Unit)
Protocol	Pelco D, Pelco P Auto Detecting
Alarm I/O	8 Input / 4 Output (Optional)
Fan/ Heater	Built In
Power Source	AC 24V, Max 1.5A
Operating Temperature	-30°C ~ 50°C
Dimensions	8.5"(W), 11"(H)

Control
from DVR

PTZ2001



PTZ2001—Wall Mount Bracket

PTZ1001



TX- PTZ (Controller)

Features

- x220 Zoom Speed Dome Day & Night Camera
- 1/4" Sony IT Super HAD CCD
- Outdoor/Indoor
- 480 TV Lines
- x22 Optical Zoom (f=3.9~85.8mm, F1.6) Video AF
- x10 Digital Zoom
- Day & Night (Min. 0.001Lux)
- Pan/Tilt Range 360°(endless), 180°(Flipover)
- Pan/Tilt Speed 360°/sec, 52°/sec
- 128 Preset Positions/Touring/Pattern



4973 Rivers Avenue
Building 300
North Charleston, SC 29406
www.tscharleston.com
(843) 745-0045 or (888) 347-3821

