

VANDAL-RESISTANT DOME CAMERA

VDO1

To order,
call
1-888-347-3821

Specifications

TV Type	NTSC
Effective Pixels	410,000
Horizontal Resolution	More than 550 TV Lines
Image Sensor	1/3" Sony Super HAD CCD
Minimum Illumination	0.3 Lux (Color), 0.1 Lux (B/W), 0.008 Lux (DSS x 32)
Scanning System	2:1 Interlace
Video Output	Composite 1.0Vp-p/75Ω, BNC Out
Electric Auto Iris	1/60 ~ 1/120,000 sec
Lens	4mm ~ 9mm Vari-focal
White Balance	Auto
AGC / BLC / D&N / FL	On / Off Selectable
Digital Slow Shutter	Max 32 times
D-Zoom	2 Times
DNR	AUTO
Input / Output Connector	Power / Video
Operating Temperature	14 F ~ 113 F
Storage Temperature	-4 F ~ 149 F
Power Consumption	AC24V / DC12V (180mA max)
Dome Size	3.937"



Features

- Color Vari-focal True D&N Outdoor Vandal Dome Camera
- Vandal-Resistant
- 1/3" Sony Super HAD CCD
- High Resolution: 550 TV Lines
- Built-in DC Iris Vari-focal Lens (f=4~9mm)
- 2.5~6mm/3.7~12mm Lens Available
- SDNR (Super Digital Noise Reduction)
- Minimum Illumination : 0.008Lux (DSS x32)
- 3-Axis Camera Construction
- DC12V , AC24V (180mA)



4973 Rivers Avenue
Building 300
North Charleston, SC 29406
www.tscharleston.com
(843) 745-0045 or (888) 347-3821

