

VANDAL-RESISTANT DOME CAMERA



VDIR1

Specifications


TV Type	NTSC
Effective Pixels	410,000
Horizontal Resolution	More than 520 TV Lines
Image Sensor	1/3" Sony Super HAD CCD
Minimum Illumination	0 Lux (50 ft. IR Illumination)
Scanning System	2:1 Interlace
Video Output	Composite 1.0Vp-p/75Ω, BNC Out
Electric Auto Iris	1/60 ~ 1/100,000 sec
Backlight Compensation	Yes
Gamma	0.45
S/N Ratio	Over 45dB (AGC Off)
White Balance	Auto
Gain Control	Auto
Lens	4~9mm Auto Iris Lens (F=1.6)
IR LED	850nm IR LED x 24 EA
CDS Sensor	IR LED On/Off Automatically
Power Source	DC 12V
Power Consumption	350mA
Operating Temperature	-20°C ~ 50°C
Operating Humidity	30 ~ 90% RH
Dimensions	4.8" (W) x 3.8" (H)



Features


- Color High Resolution Outdoor Dome Camera
- Vandal-Resistant, Vari-Focal Auto-Iris
- 1/3" Sony Super HAD CCD
- 520 TV Lines
- 24 IR LED (On/Off Automatically)
- Min. 0 Lux (50 ft. IR Illumination)
- External Vari-Focal Lens Adjustment
- Gimbal 3 Axis (Pan / Tilt / Twist)

External Zoom/Focal Adjustment



Tilting Up to 10° ~ 90°

Panning Up to 360°



4973 Rivers Avenue
Building 300
North Charleston, SC 29406
www.tscharleston.com
(843) 745-0045 or (888) 347-3821

